

80's and Newer Chain Stock AND 2 Man Extreme Rules

1. All station wagon decking must be removed
2. Windshield bar is required 2 max. 3" wide max Attached to roof and firewall, no more than 6"
3. One down bar is allowed off of door bars inside only on each side of car to help prevent drivers/batteries, Etc. from being hit. Attached to floor sheet metal only body bolts must remain factory, unaltered in stock metal only
4. All chrome strips, door handles etc. Must be removed from car
5. All trailer hitches must be completely removed.
6. Shocks and leaf springs must be in original condition, not homemade. NO extra clamps.
7. NO welding of frames. NO welding of any type unless stated in these rules. A-arms may be bolted or chained or weld 1" wide strap 4" long and 2 per arm
8. NO displaying foul, profane, or suggestive wording or decorations. You will be required to paint or remove infraction
9. Any automotive bumper may be used, cut to fit. NO homemade bumpers/brackets
10. Bumpers may be welded on. Bumper to factory shocks/brackets, factory shocks/brackets to frame. One set of brackets only. Bumper brackets must be factory to make and model of car. Bumper skin may also be welded down 5 on 5 off with no added material.
11. Hood must remain in stock position
12. A minimum of a 6" hole must be cut in hood for fire dept. header holes are ok
13. Radiator must be in stock position. Ratchet straps or wire to hold in place, do not use bolts
14. Floor shifters are ok

15. Motor and transmission may be welded in place. Do not reinforce frame or you will cut. Official's decision

16. No distributor protectors

17. External tranny coolers will be allowed. Must be securely mounted on floor. Lines must be rated for high pressure. DO NOT just use fuel lines with hose clamps

18. Drivers door may be welded shut solid, ONLY drivers door

19. Drivers and passengers door bars ok connected from dash bar to seat bar. Bars cannot be more than 60" in length

20. All other doors may be chained or wired in 2 locations per seam

21. 2 bumper ties (chain or wire only) allowed front and rear, Must be in place during inspection

22. Trunk lids may be tucked in leave 60% in factory location

23. Maximum of 10 gallons of gas allowed

24. Gas tanks must be inside car, mounted in the rear seat area, Must be securely fastened down. Do not use plumbers tape with self tappers. Gas tank protectors are allowed must be 1 inch from the back and 3 inches from the floor. Official's decision is final.

25. Splash cover is recommended

26. Do not use gas lines under the car

27. No non-metal containers. Boat tanks or well made fuel cells highly recommended

28. Doubled or flapped tires are ok

29. Stem protectors are ok

30. Remove all wheel weights

31. Any stock 5 lug rear end may be used. NO bracing or after market axles (stock class only)

32. Rear end may be welded for posi traction
33. Limit of 2 batteries. Must be securely fastened and covered on front passenger floor
34. No studded tires or wheel weights.
35. Lower engine cradles with front plate ok. Must be bolted to motor and no pulley protectors
36. All suspension must remain stock and no reinforced tie rods
37. Your allowed 6 bolts, chains, or 9 wire to secure hood and trunk only 2 bolts can go to frame thru core support only and 2 to frame in trunk 3/4" max on bolts in hood and trunk
38. You may tilt frames cold bend only, DO NOT cut and weld
39. Max tire size 15"
40. Max bumper height of 21" to bottom with a min. of 15" to bottom
41. Slider driveshaft's are ok.